

# Portable Emergency Lights W 270.3/4, W 270.3/7 and Charging Unit Z 345.3 with Emergency Lighting Function



W 270.3/4  
Separate charging unit

## Technical data

### W 270.3/4, W 270.3/7 with emergency lighting function for separate charging unit

|  |   |
|--|---|
| Slip-on filters (incl.)                            | red, orange, white  |
| Enclosure material                                 | impact resistant, non-adhesive plastic  |
| Enclosure colour                                   | grey  |
| Duration of emergency lighting Battery 4 Ah (7 Ah) | 3.5 h (6.5 h) with incandescent lamp 5 V/5 W (main)<br>12.0 h (25 h) with incandescent lamp 4.8 V/1.5 W (pilot) |
| Battery  | rechargeable, maintenance free, gas tight<br>NC-Akku 4.8 V / 4 Ah<br>NC-Akku 4.8 V / 7 Ah                       |
| Lamp   | Main beam 5 V / 5 W<br>Pilot beam 4.8 V / 1.5 W   |
| Insulation class                                   | II  |
| Degree of protection                               | IP 54   |
| Switch function                                    | Flashlight, maintained light and pilot light  |

## Ordering details

| Type      | Battery | Order No.      |
|-----------|---------|----------------|
| W 270.3/4 | 4 Ah    | 1 1145 000 270 |
| W 270.3/7 | 7 Ah    | 1 1145 000 272 |

## Accessories

| Accessories/spare part   | Order No.                        |
|--|----------------------------------|
| Incandescent lamp<br>-5 V / 5 W (5 pcs.)<br>-4.8 V / 1.4 W (10 pcs.) | 4 0071 345 265<br>4 0071 345 264 |
| Rechargeable NiCd-accu. 4,8 V/4 Ah                                   | 4 0071 345 248                   |
| Rechargeable NiCd-accu. 4,8 V/7 Ah                                   | 4 0071 345 253                   |
| Slip-on filter set red, orange and radial difuser cap                | 2 1145 995 000                   |

## Lighting engineering

see page 7/28

## Technical Data

### Z 345.3 for portable emergency lights W 270.3

|                      |  |
|----------------------|--|
| Enclosure material   | impact resistant, non-adhesive plastic |
| Enclosure colour     | grey                                   |
| Rated voltage        | 230 V 50/60 Hz                         |
| Rated load           | 10 VA                                  |
| Insulation class     | II                                     |
| Degree of protection | IP 44                                  |

## Ordering details

| Type                  | Order No.      |
|-----------------------|----------------|
| Charging unit Z 345.3 | 4 0071 341 145 |



Charging unit Z 345.3  
for portable emergency lights  
W 270.3/4 and W 270.3/7